MALZEME GÜVENLİK BİLGİ FORMU

(MATERIAL SAFETY DATA SHEET)

UAT 2

2024

BÖLÜM 1: Maddenin/karışımın kimliği

Tedarikçi Firma;

MBI RULMAN VE MAK.SAN.TİC.LTD.ŞTİ.
1230/1 SOKAK NO:44 Ostim / ANKARA
+90 312 354 98 08

1.1 Madde/Karışımın kimliği

Ticari ismi : **UAT 2**

1.2 Madde veya karışımın belirlenmiş kullanımları ve tavsiye edilmeyen kullanımları

Madde/Karışımın kullanımı : Otomotiv ve sanayi gresi.

1.3 Acil durum telefon numarası

Acil durum telefon numarası : (+90)212 376 00 00
Ulusal Zehir Danışma Merkezi (UZEM) - 114

BÖLÜM 2: Zararlılık tanımlanması

2.1 Madde veya karışımın sınıflandırılması

Sınıflandırma T.R. SEA No 28848
Mevcut verilere dayalı olarak, bu madde / karışım sınıflandırma kriterlerini karşılamıyor.

2.2 Etiket unsurları

Etiketleme T.R. SEA No 28848

Zararlılık İşaretleri : Zararlılık işareti yok

Uyarı Kelimesi : Uyarı kelimesi yok

Zararlılık ifadeleri : FİZİKSEL ZARARLILIKLAR:
SEA sınıflandırma kriterleri kapsamında fiziksel açıdan zararlı olarak sınıflandırılmaz.
SAĞLIK ZARARLILIKLARI:

SEA sınıflandırma kriterleri kapsamında sağlık açısından zararlı olarak sınıflandırılmaz.
ÇEVRESEL ZARARLILIKLAR:
SEA sınıflandırma kriterleri kapsamında çevre açısından zararlı olarak sınıflandırılmaz.

Önlem ifadeleri : Önlem:
İhtiyati ibareler bulunmamaktadır.
Müdahale:
İhtiyati ibareler bulunmamaktadır.
Depolama:
İhtiyati ibareler bulunmamaktadır.
Bertaraf:
İhtiyati ibareler bulunmamaktadır.

Hassasiyet yapıcı bileşenler : Alkil tiyadiyozol içerir.
Triazol türevleri içerir.
Çinko naftenat içerir.
Alerjik reaksiyona yol açabilir.

2.3 Diğer zararlar

Gereği gibi temizlemeden cildin uzun süreli veya tekrarlı biçimde maruzkalması derideki gözenekleri kapatarak yağ aknesi/folikülit gibibozukluklara neden olabilir.
Kullanılmış gres zararlı kirleticiler içerebilir.
Deri altına yüksek basınçta enjeksiyonu, yerel kangren dahil ciddi zarara neden olabilir.
Alevlenir olarak sınıflandırılmıyor ama yanıcı.

BÖLÜM 3: Bileşimi/İçindekiler hakkında bilgi

3.2 Karışımlar

Kimyasal yapısı

Yüksek derecede rafine olmuş mineral yağı ve katkı maddeleri içeren yağlayıcı gres.
Yüksek oranda rafine edilmiş mineral yağı, IP346'ya göre <%3 (ağırlıkça) oranında DMSO özü içerir.
DMSO ekstrakt içeriğine göre sınıflandırma < %3 (Yönetmelik (TC) 28848/2013, Ek VI, Not L).

Zararlı bileşenler

Kimyasal İsmi	CAS-No. EC-No. Kayıt numarası	T.R. SEA No 28848	Konsantrasyon (% w/w)
Çinko Naftenat	12001-85-3 234-409-2/01 2120783834-41	Cilt Hassas.1; H317 GözTah.2; H319 Sucul Kronik2; H411	0,1 - 0,9
Triyazol türevi	91273-04-0	Cilt Aşnd.lB; H314	0,01 - 0,09

	401-280-0	Cilt Hassas.1A; H317 Sucul Kronikl; H410	
Alkil tiyadiyozol	13539-13-4 236-912-2	Cilt Tah.2; H315 Cilt Hassas.1A; H317 Akut Tok.4; H332 Sucul Kronik4; H413	<0,09

Kısaltmaların açıklamaları için 16.bölüme bakınız.

BÖLÜM 4: İlk yardım önlemleri

4.1 İlkyardım önlemlerinin açıklaması

İlk yardım yapanların güvenliği : İlk yardım uygularken, olay, yaralanma ve çevrede bulunanlara göre uygun kişisel koruyucu ekipman giydiğinizden emin olun.

Solunması halinde : Normal kullanım koşullarında tedavi gerektirmez.
Eğer belirtiler devam ederse, bir sağlık kuruluşuna başvurun.

Deriyle teması halinde : Bulaşmış giysileri çıkarın. Maruz kalmış bölgeye su dökün ve şayet varsa sabunla yıkamaya devam edin.
Kalıcı bir tahriş oluşmuşsa tıbbi yardıma başvurun.

Yüksek basınçlı ekipman kullanılırken, ürün derinin altına enjekteolabilir. Yüksek basınçtan kaynaklanan yaralanma olursa, yaralı hemenhastaneye gönderilmelidir. Belirtilerin ortaya çıkmasını beklemeyin.
Görünürde bir yara olmasa bile, tıbbi yardım alın.

Gözle teması halinde : Bol suyla gözleri yıkayın.
Kontakt lens, varsa ve çıkarması kolaysa, çıkarın. Sürekli durulayın.
Kalıcı bir tahriş oluşmuşsa tıbbi yardıma başvurun.

Yutulması halinde : Büyük miktarlarda yutulmadığı takdirde, genellikle tedaviye gerek yoktur, bununla birlikte, tıbbi tavsiye alın.

4.2 Akut ve sonradan görülen önemli belirtiler ve etkiler

Belirtiler : Maruz kalan bölgelerde deri üzerinde siyah kabarcık ve noktaların görülmesi yağ aknesi/folikülit belirtilerindendir Ağızdan alınması durumunda, bulantı, kusma ve/veya ishale neden olabilir.

Enjeksiyondan sonra birkaç saat içinde acının gecikmesi ve dokunun zarar görmesinin başlamasıyla yerel kangren olduğu ispatlanmıştır.

4.3 Tıbbi müdahale ve özel tedavi gereği için ilk işaretler

Tedavi : Doktor notları:
Semptomlara göre bir tedavi uygulayın.

Yüksek basınçta enjeksiyon yoluyla oluşmuş yaralarda, doku hasarını veişlev kaybını en aza indirmek için hemen ameliyatla müdahale vemuhtemelen steroid tedavisi gerekir. Giriş yaraları küçük olduğundan ve hasarın ciddiyetini yansıtmadığından durumun ciddiyetini tespit etmek için ameliyat gerekebilir. Şişme, damar kasılması ve iskemiye neden olabileceğinden yerel anestezi ve sıcak ıslatmadan kaçınılmalıdır. Genel anestezi altında, anında ameliyatla basıncın giderilmesi ve tüm yabancı cisimlerle hasar görmüş dokunun çıkartılması gerçekleştirilmeli ve durum kapsamlı biçimde araştırılmalıdır.

BÖLÜM 5: Yangınla mücadele önlemleri

5.1 Yangın söndürücüler

Uygun yangın söndürücüler : Köpük, su püskürtme veya su zerrecikleri. Kuru kimyasal toz, karbon dioksit, kum ve toprak sadece küçük yangınlarda kullanılabilir.

Uygun olmayan söndürme aracı : Fıskiyede su kullanmayınız.

5.2 Madde veya karışımdan kaynaklanan özel zararlar

Yangın söndürme sırasında oluşabilecek özel zararlar : Tehlikeli yanma ürünleri şunları içerebilir:
Havadaki katı ve sıvı partiküllerle gazın (duman) kompleks bir karışımı.
Yanma tamamlanmazsa karbon monoksit ortaya çıkabilir.
Tanımlanmamış organik ve inorganik bileşikler.

5.3 Yangın söndürme ekipleri için tavsiyeler

Yangın söndürme ekibi için özel koruyucu ekipmanlar : Kimyasal maddelere dayanıklı eldivenler dahil uygun ekipmanlar kullanılmalıdır; dökülen ürünle büyük çaplı bir temas bekleniyorsa kimyasal maddelere dayanıklı takım giyilmesi belirtilmiştir. Kapalı bir alanda ateşe yaklaşırken Bağımsız Solunum Aparatı takılmalıdır. İlgili standartlar uyarınca onaylanmış itfaiyeci kıyafeti seçin (örn. Avrupa: EN469).

Özel yangın söndürme yöntemleri : Yerel şartlar ve çevre için uygun yangın söndürme yöntemleri kullanınız.

BÖLÜM 6: Kaza sonucu yayılmaya karşı önlemler

6.1 Kişisel önlemler, koruyucu donanım ve acil durum prosedürleri

Kişisel önlemler : Deriyle ve gözlerle temas etmesinden kaçının.

6.2 Çevresel önlemler

Çevresel önlemler : Çevre kirliliğini önlemek için, zararlı maddeleri kontrol altındatutacak uygun bir sistem kullanın. Tuz, toprak veya diğer uygunbariyerleri kullanarak, kanalizasyon, su kanalı veya nehirleredökülmesini ya da karışmasını engelleyin.

6.3 Muhafaza etme ve temizleme için yöntemler ve materyaller

Temizleme yöntemleri : Kum, toprak veya diğer uygun engeller kullanarak kanallara, rögarlara ve akarsulara sızmasını önleyin.

6.4 Diğer bölümlere atıflar

Kişisel koruyucu ekipman seçimi için Güvenlik Bilgi Formunun 8. Bölümüne bakın.,, Döküntülerin bertarafı için Güvenlik Bilgi Formunun 13. Bölümüne bakın.

BÖLÜM 7: Elleçleme ve depolama

7.1 Güvenli elleçleme için önlemler

Teknik önlemler : Buhar, sis ve aerosolların solunması riski varsa, yerel egzos havalandırmayı kullanın.
Bu veri föyündeki bilgileri, bu malzemenin güvenli bir biçimde elleçlenmesi, depolanması ve atılması için uygun kontrollerin belirlenmesine yardımcı olmak üzere, yerel koşullara ilişkin bir risk değerlendirmesinde girdi olarak kullanın.

Güvenli elleçleme önerileri : Deriyle uzun süreli veya tekrarlı temasdan kaçının.
Buhar ve/veya buğu solumaktan kaçının.
Fıçılardaki ürün ele alınırken, koruyucu ayakkabılar giyilmeli ve uygun ele alma ekipmanı kullanılmalıdır.
Yangınları önlemek için bulaşmış bütün bezleri veya temizlik malzemelerini uygun bir şekilde atın.

7.2 Uyuşmazlıkları da içeren güvenli depolama için koşullar

Diğer veriler : Konteyneri serin ve iyi havalandırılmış bir yerde ağzı sıkıca kapalı olarak saklayın. Uygun biçimde etiketlenmiş ve kapatılabilen konteynerler kullanın.

Ortam sıcaklığında saklayın.

Bu ürünün ambalajlanması ve saklanmasına dair bilgileri içeren bir ek spesifik yönetmelik için bölüm 15'e bakın.

Paketleme malzemesi : Uygun malzeme: Konteyner veya konteyner astarları için, orta karbonlu çelik veya yüksek yoğunluklu polietilen kullanın.
Uygun olmayan malzeme: PVC.

7.3 Belirli son kullanımlar

Özel kullanım(lar) : Uygulanamaz

BÖLÜM 8: Maruz kalma kontrolleri/kişisel korunma

8.1 Kontrol parametreleri

Mesleki maruziyet sınırları

Bileşenleri	CAS-No.	Değer tipi (Maruz kalma şekli)	Kontrol parametreleri	Esaslar
Yağ Buharı, mineral		TWA	5 mg/m3	ABD. ACGIH Eşik Sınır Değerleri

Biyolojik maruz kalma limitleri

Belirlenen herhangi bir biyolojik sınır yoktur.

8.2 Maruz kalma kontrolleri

Mühendislik önlemleri

Koruma düzeyi ve gerekli kontrollerin tipleri potansiyel maruk kalma koşullarına bağlı olarak farklılık gösterecektir. Yerel koşullara ilişkin bir risk değerlendirmesine dayanarak kontrolleri seçiniz. Uygun önlemler şunları içerir:
Havadaki konsantrasyonları kontrol altına almak için yeterli havalandırma.

Maddenin ısıtıldığı, püskürtüldüğü veya buğu haline getirildiği ortamlarda, havada oluşan konsantrasyonların artma potansiyeli daha yüksektir.

Genel bilgiler:
Kontrollerin güvenli kullanımı ve bakımı için prosedürler belirleyin.
Bu ürünle ilgili normal etkinliklere ilişkin tehlike ve kontrol önlemleri konusunda çalışanları eğitin. Kişisel koruyucu ekipman, yerel egzoz havalandırması gibi maruz kalma durumunu kontrol etmek için kullanılan ekipmanın doğru seçildiğinden, test edildiğinden ve bakımının yapıldığından emin olun.
Ekipmanı açmadan veya bakımdan önce sistemikapatın.
Atıkları tasfiye edinceye veya sonra yeniden değerlendirinceye kadar mühürlü olarak saklayın. Malzemeyi kullandıktan sonra ve yemek yemeden, içki içmeden ve/veya sigara içmeden önce elleri yıkamak gibi iyi kişisel hijyen önlemlerini her zaman alın. Kirden arınması için iş kıyafetlerini ve koruyucu ekipmanı düzenli olarak temizleyin. Temizlenemeyen kirli kıyafetleri ve ayakkabıları atın. İyi bir bakım ve temizlik yapın.
Ürünün yarı katı kıvamında olmasından ötürü, buhar veya toz oluşumu olası değildir.

Kişisel koruyucu ekipmanlar

Gözlerin korunması : Eğer malzeme göze sıçrayabilecek bir şekilde taşınıyorsa, koruyucu gözlük tavsiye edilir.

Ellerin korunması		
Notlar	:	Ürünle el temasının meydana gelebileceği durumlarda, ilgili standartlara (örn., Avrupa: EN374, ABD: F739) göre onaylanmış, aşağıdaki malzemeden yapılma eldivenlerin kullanılması uygun kimyasal koruma sağlayabilir: PVC, neopren veya nitril plastik eldiven. Bir eldivenin uygunluğu ve dayanıklılığı, kullanıma, yani temasın sıklığı ve süresi, eldiven malzemesinin kimyasal direnci ve el ve parmakların içinde ustalıkla kullanılabilmesine bağlıdır. Eldiven tedarikçilerinden daima tavsiye alın. Kirlenmiş eldivenler değiştirilmelidir. Etkin el bakımı sağlamak için bireysel hijyen önemlidir. Eldivenleryalnızca eller temizken giyilmelidir. Eldivenleri kullandıktan sonra,eller iyice yıkanmalı ve kurulanmalıdır. Parfüm içermeyen birnemlendiricinin kullanılması önerilir. 240 dakikadan fazla tercihen > 480 dakikalık hamle zamanı sırasında sürekli temas etme halinde uygun eldivenlerin kullanılmasını öneririz. Kısa süreli/sıçramadan korunma için aynı önlemin alınmasını öneririz ancak bu koruma seviyesinde sunulan uygun eldivenlerin kullanılmayabileceğini unutmayın ve bu durumda uygun bakım ve değiştirme rejimleri izlendiği sürece daha düşük hamle zamanı kabul edilebilir. Eldiven materyalinin tam kompozisyonuna bağlı olduğundan eldivenin kalın olması kimyasallara dayanıklı iyi bir koruyucu özelliğe sahip olduğunu göstermez. Eldiven kalınlığı, eldiven markası ve modeline bağlı olarak genellikle 0,35 mm'den fazla olmalıdır.
Deri ve vücudun korunması	:	Standart iş giysilerinin ötesinde cilt koruması olağan koşullarda gerekli değildir. Kimyasallara dayanıklı eldiven giyilmesi iyi bir uygulamadır.
Solunum sisteminin korunması	:	Normal kullanım koşulları altında genellikle solunum korunmasına ihtiyaç yoktur. İyi sınai hijyen yöntemlerine uygun olarak, madde solunmasını önlemek için önlem alınmalıdır. Havadaki konsantrasyonun işçi sağlığını korumak için yeterli derecede ko ntrol edilemediği yerlerde, ilgili yerin şartlarına göre seçilmiş ve yerel mevzuata uygun koruyucu nefes cihazları kullanın. Koruyucu nefes cihazları tedarikçileri ile durumu görüşün. Hava filtreli nefes cihazlarının kullanılabildiği yerlerde uygun bir maske-filtre İkilisi seçin. Organik gazlar ve buharlar ve parçacıkların kombinasyonuna uygun bir filtre seçin [Tip A/Tip P kaynama noktası >65°C (149°F)].
Koruyucu tedbirler	:	Kişisel koruyucu donanımı (KKD) önerilen ulusal standartlara uymalıdır. KKD tedarikçilerinden kontrol edin.

Termal tehlikeler : Uygulanamaz

Çevresel maruz kalma kontrolleri

Genel öneri : İlgili çevre koruma mevzuatının gereklerini yerine getirmek için uygun tedbirleri alınız.Bölüm 6'da verilen tavsiyeler doğrultusunda çevrenin kirlenmesini önleyin.Gerektiğinde çözünmemiş maddelerin atık suya deşarj edilmesini engelleyin.Atık su,yüzey suyuna deşarj edilmeden önce bir belediye veya endüstriyel atık su arıtma tesisinde işlemden geçirilmelidir.#
Buhar içeren havanın dışarı atılmasında, tehlikeli maddelerin emisyonuna ilişkin yerel şartlara uyulmalıdır.

BÖLÜM 9: Fiziksel ve kimyasal özellikler

9.1 Temel fiziksel ve kimyasal özellikler hakkında bilgi

Görünüm	: Oda sıcaklığında yarı-katı halde bulunur.
Renk	: Açık kahverengi
Koku	: Hafif hidrokarbon
Koku Eşiği	: Herhangi bir veri bulunmamaktadır
PH	: Uygulanamaz
Damlama noktası	: 180°C Metod: İP 396
Erime / donma noktası	Uygulanmaz
Başlangıç kaynama noktası ve kaynama aralığı	: Herhangi bir veri bulunmamaktadır
Parlama noktası	: Uygulanmaz
Buharlaşma oranı	: Herhangi bir veri bulunmamaktadır
Alevlenirlik (katı, gaz)	: Herhangi bir veri bulunmamaktadır
Üst patlayıcı limiti	: Tipik 10 %(V)
Alt patlayıcı limiti	: Tipik 1 %(V)
Buhar basıncı	: < 0,5 Pa (20 °C) tahmini değer(ler)

Bağıl buhar yoğunluğu	: > 1 tahmini değer(ler)
Bağıl yoğunluk	: 0,900 (15 °C)
Yoğunluk	: 900 kg/m3 (15,0 °C) Metod: Belirsiz
Çözünürlük(ler)	
Su içinde çözünürlüğü	: ihmal edilebilir
Diğer çözücüler içindeki çozunurıuıugu	: Herhangi bir veri bulunmamaktadır
Dağılım katsayısı (n- oktanol/su)	: log Pow: > 6 (benzer ürünlerle ilgili bilgilere göre)
Alev alma sıcaklığı	: > 320 °C
Bozunma sıcaklığı	: Herhangi bir veri bulunmamaktadır
Akışkanlık	
Akışkanlık (viskozite, dinamik)	: Herhangi bir veri bulunmamaktadır
Kinematik viskozite	: Uygulanamaz
Patlayıcılık özellikleri	: Sınıflandırılmamıştır
Oksitleyici özellikler	: Herhangi bir veri bulunmamaktadır

9.2 Diğer bilgiler

Yüzey gerilimi	: Herhangi bir veri bulunmamaktadır
İletkenlik	: Bu malzemenin statik bir toplayıcı olmadığı düşünülmektedir.

BÖLÜM 10: Kararlılık ve tepkime

10.1 Tepkime

Ürün, aşağıdaki alt paragrafta belirtilenlerin yanı sıra ek reaktivite tehlikelerine neden olmaz.

10.2 Kimyasal kararlılık

Kararlı.

10.3 Zararlı tepkime olasılığı

Zararlı tepkimeler : Kuvvetli oksidanlarla reaksiyona girer.

10.4 Kaçınılması gereken durumlar

Kaçınılması gereken durumlar : Aşırı ısı düzeyleri ve doğrudan güneş ışığı.

10.5 Kaçınılması gereken maddeler

Kaçınılması gereken maddeler : Güçlü oksitleyici reaktifler.

10.6 Zararlı bozunma ürünleri

Belirtildiği şekilde kullanıldığında ve saklandığında bozunma olmaz.

BÖLÜM 11: Toksikolojik bilgiler

11.1 Toksik etkiler hakkında bilgi

Olası maruz kalma yolları hakkında bilgiler	Esas maruz kalma yolları cilt veya göz teması olsa da, kazara yutma durumunda da maruziyet meydana gelebilir.

Akut toksisite

Ürün:

Ağız yoluyla Akut toksisite	LD50 (sıçan): > 5.000 mg/kg Notlar: Düşük toksisite: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.
Akut solunum(inhalasyon) toksisitesi	Notlar: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.
Cilt yoluyla Akut toksisite	LD50 (tavşan): > 5.000 mg/kg Notlar: Düşük toksisite: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Cilt aşınması/tahrişi

Ürün:

Notlar: Deriyi hafif derecede tahriş eder.
Gereği gibi temizlemeden cildin uzun süreli veya tekrarlı biçimde maruzkalması derideki gözenekleri kapatarak yağ aknesi/folikülit gibibozukluklara neden olabilir.
Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Ciddi göz hasarı/göz tahrişi

Ürün:

Notlar: Gözleri hafif derecede tahriş eder.
Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Solunum veya cilt hassaslaştırıcılığı

Ürün:

Notlar: Deride hassasiyet yaratmaz.
Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Bileşenleri:

Triyazol türevi:
Notlar: Duyarlı kişilerde alerjik deri reaksiyonuna neden olabilir.

Eşey hücre mutajenitesi

Ürün:

İn vivo genotoksisite : Notlar: Mutajenik değildir
Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Kanserojenite

Ürün:

Notlar: Kanser yapıcı değildir.
Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Notlar: Ürün, hayvan derisi boyama çalışmalarında kanserojen olmayan tipte olduğu gösterilmiş mineral yağları içermektedir.
Yüksek derecede rafine madeni yağlar, Uluslararası Kanser Araştırmaları Kurumu (İARC) tarafından karsinojen olarak sınıflandırılmamaktadır.

Malzeme	GHS/CLP Kanserojenite Sınıflandırma
Yüksek oranda rafine edilmiş mineral yağı	Karsinojenite sınıflandırması yok

Üreme sistemi toksisitesi

Ürün:

Doğurganlığa olan etkileri
Notlar: Birikmeli birtoksik madde değildir.
Üretkenlikte bozulmaya yol açmaz.
Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Belirli Hedef Organ Toksisitesi-tek maruz kalma

Ürün:

Notlar: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Belirli Hedef Organ Toksisitesi -tekrarlı maruz kalma

Ürün:
Notlar: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Aspirasyon zararı

Ürün:
Solunum tehlikesi yoktur., Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Ek bilgi

Ürün:
Notlar: Kullanılmış gres, kullanım sırasında birikmiş zararlı kirleticileriçerebilir. Bu türlü zararlı kirleticilerin konsantrasyonu, kullanımabağlıdır ve bertaraf edildiklerinde sağlık ve çevre açısından riskteşkil edebilirler. Kullanılmış TÜM gres dikkatle taşınmalıdır ve ciltle temasından mümkün olduğunca kaçınılmalıdır.

Notlar: Ürünün yüksek basınçla deri içine enjeksiyonu, eğer ürün ameliyatla alınmazsa, yerel kangrene neden olabilir.

Notlar: Solunum sistemini hafifçe tahriş eder

BÖLÜM 12: Ekolojik bilgiler

12.1 Toksisite

Ürün:

Balıklar üzerinde toksisite (Akut toksisite)	:	Notlar: LL/EL/IL50 > 100 mg/l Hemen hemen hiç toksik değildir: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.
Daphnia ve diğer suda yaşayan omurgasızlar üzerinde toksisite (Akut toksisite)	:	Notlar: LL/EL/IL50 > 100 mg/l Hemen hemen hiç toksik değildir: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.
Su yosunları (algler) üzerinde toksisite (Akut toksisite)	:	Notlar: LL/EL/IL50 > 100 mg/l Hemen hemen hiç toksik değildir: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.
Balıklar üzerinde toksisite (Kronik toksisite)	:	Notlar: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.
Daphnia ve diğer suda	:	Notlar: Mevcut bilgilere dayanarak, sınıflandırma kriterleri

yaşayan omurgasızlar üzerinde toksisite (Kronik toksisite) — yerine gelmemektedir.

Bakteriler üzerinde toksisite (Akut toksisite) — Notlar: Mevcut bilgilere dayanarak, sınıflandırma kriterleri yerine gelmemektedir.

Bileşenleri:

Triyazol türevi:

M-Faktörü (Kısa süreli (akut) sucul zararlılık) : 1

M-Faktörü (Uzun (kronik) süreli sucul zararlılık) : 1

12.2 Kalıcılık ve bozunabilirlik

Ürün:

Biyolojik bozunabilirlik : Notlar: Kolay bozunmaz.
Belli başlı bileşenler kendiliğinden biyolojik olarak parçalanabilirancak doğada parçalanmaya karşı dirençli bileşenler içermektedir.

12.3 Biyobirikim potansiyeli

Ürün:

Biyobirikim : Notlar: Biyoakümüle olma potansiyeli taşıyan bileşenler.

12.4 Toprakta hareketlilik

Ürün:

Hareketlilik (Mobilité) : Notlar: Oda sıcaklığında yarı-katı halde bulunur., Toprağa karışırsa, toprak partiküllerine yapışır ve hareketliliğini yitirir.

Notlar: Su üstünde yüzer.

12.5 PBT ve vPvB değerlendirmesinin sonuçları

Ürün:

Değerlendirme : Bu karışım, PBT veya vPvB olarak değerlendirilen REACH onaylı hiçbir madde içermez..

12.6 Diğer olumsuz etkiler

Ürün:

Ekolojiyle ilgili ek bilgiler : Notlar: Ozon seyreltici pontasiyele, fotokimyasal ozon oluşturma potansiyeline ya da küresel ısınma potansiyeline sahip değildir.

Ürün, normal kullanım koşulları altında havaya ciddi miktarda salınmayan uçucu nitelikte olmayan bileşenlerin bir karışımıdır.

Notlar: Çözünürlüğü kötü bir karışım.
Akuatik organizmalar için fiziksel kirlenmeye neden olur.

Notlar: Mineral yağ, 1 mg/l altındaki yoğunluklarda akutaik organizmalarda kronik toksisiteye neden olmaz.

BÖLÜM 13: Bertaraf etme bilgileri

13.1 Atık işleme yöntemleri

Ürün

: Mümkünse geri kazanın veya geri dönüştürün.
Yürürlükteki yönetmelikler uyarınca uygun atık sınıflandırması ve atma yöntemlerine karar vermek üzere, oluşan materyalin toksitivite fiziksel özelliklerini belirleme sorumluluğu atığı üreten tarafa aittir.
Atık ürünün, toprak ya da yeraltı sularını kirletmesine izin verilmemeli ya da çevreye bırakılarak bertaraf edilmemelidir. Çevreye, kanalizasyona veya akarsulara atmayın.
Toprağa drenajına izin vererek tank dibinde biriken suyu bertaraf etmeyin. Bu, toprak ve yeraltı sularının kirlenmesine yol açacaktır.
Bir döküntü veya tank temizliğinden kaynaklanan atıklar yürürlükteki yönetmeliklere uygun olarak elden çıkarılmalı, tercihen tanınan bir toplayıcı veya taşerona teslim edilmelidir. Toplayıcı veya taşeronun yetkinliği önceden saptanmalıdır.

MARPOL - Gemi kaynaklı kirliliğin denetlenmesine dair teknik hususları sunan, Gemilerden Kaynaklanan Kirliliğin Önlenmesi Uluslararası Sözleşmesi'ne (MARPOL 73/78) bakın.

Kontamine ambalaj

: Yürürlükteki yönetmeliklere uygun olarak elden çıkarınız, tercihen tanınan bir toplayıcı veya taşerona teslim ediniz. Toplayıcı veya taşeronun yetkinliği önceden saptanmalıdır. Atıkların elden çıkarılması yürürlükteki bölgesel, ulusal ve yerel yasa ve yönetmeliklere uygun olmalıdır.

BÖLÜM 14: Taşımacılık bilgileri

14.1 UN Numarası

ADR	: Tehlikeli madde olarak düzenlenmemiştir
RID	: Tehlikeli madde olarak düzenlenmemiştir
IMDG	: Tehlikeli madde olarak düzenlenmemiştir
IATA	: Tehlikeli madde olarak düzenlenmemiştir

14.2 Uygun UN taşımacılık adı

ADR	: Tehlikeli madde olarak düzenlenmemiştir
RID	: Tehlikeli madde olarak düzenlenmemiştir
IMDG	: Tehlikeli madde olarak düzenlenmemiştir
IATA	: Tehlikeli madde olarak düzenlenmemiştir

14.3 Taşımacılık zararlılık sınıf(lar)ı

ADR	: Tehlikeli madde olarak düzenlenmemiştir
RID	: Tehlikeli madde olarak düzenlenmemiştir
IMDG	: Tehlikeli madde olarak düzenlenmemiştir
IATA	: Tehlikeli madde olarak düzenlenmemiştir

14.4 Ambalajlama grubu

ADR	: Tehlikeli madde olarak düzenlenmemiştir
RID	: Tehlikeli madde olarak düzenlenmemiştir
IMDG	: Tehlikeli madde olarak düzenlenmemiştir
IATA	: Tehlikeli madde olarak düzenlenmemiştir

14.5 Çevresel zararlar

ADR	: Tehlikeli madde olarak düzenlenmemiştir
RID	: Tehlikeli madde olarak düzenlenmemiştir
IMDG	: Tehlikeli madde olarak düzenlenmemiştir

14.6 Kullanıcı için özel önlemler

Notlar	: Özel uyarılar: Ulaşımla bağlantılı uygulamalarda kullanılması durumunda kullanıcının bilmesi ya da uyması gereken özel önlemler için bkz. "Elleme ve Depolama" başlıklı 7. Bölüm.

14.7 MARPOL 73/78 ek II ve IBC koduna göre dökme taşımacılık

Olduğu gibi temin edilmiş ürünler için geçerli değildir. Deniz yoluyla toplu sevkıyatlarda MARPOL kuralları geçerlidir.

BÖLÜM 15: Mevzuat bilgileri

15.1 Madde veya karışıma özgü güvenlik, sağlık ve çevre mevzuatı

Diğer kurallar	: Mevzuat bilgilerinin kapsamlı olması amaçlanmamaktadır. Bu materyal için diğer yönetmelikler geçerli olabilir Kimyasal maddelerle çalışmalarda sağlık ve güvenlik önlemleri hakkında yönetmelik. Binaların yangından korunması hakkında yönetmelik. Büyük endüstriyel kazaların önlenmesi ve etkilerinin azaltılması hakkında yönetmelik.

Bu ürünün içerikleri şu envanterlerde yer almaktadır:

EINECS	: Bütün bileşenler listelenmiştir ya da polimer bulunmamaktadır.
TSCA	: Bütün bileşenler listelenmiştir.

BÖLÜM 16: Diğer bilgiler

H-İbareleri tüm metni

H314	Ciddi cilt yanıklarına ve göz hasarına yol açar.
H315	Cilt tahrişine yol açar.
H317	Alerjik cilt reaksiyonlarına yol açar.
H319	Ciddi göz tahrişine yol açar.
H332	Solunması halinde zararlıdır.
H410	Sucul ortamda uzun süre kalıcı, çok toksik etki.
H411	Sucul ortamda uzun süre kalıcı, toksik etki.
H413	Sucul ortamda uzun süre kalıcı, zararlı etki yapabilir.

Diğer kısaltmaların tüm metni

Akut Tok.	Akut toksisite
Cilt Aşnd.	Ciltte Aşınma
Cilt Hassas.	Cilt hassaslaştırıcı
Cilt Tah.	Cilt tahrişi
Göz Tah.	Göz tahrişi
Sucul Kronik	Uzun (kronik) süreli sucul zararlılık

Ek bilgi

Diğer bilgiler : Sol kenarda yer alan dikey çubuk (|) önceki versiyondan bir değişikliği göstermektedir.

Bu Güvenlik Bilgi Formundaki bilgiler hazırlandığı tarihteki mevcut en iyi tecrübe, bilgi ve inançlarımız temel alınarak hazırlanmıştır ve tamlık ya da kesinlik garantisi olarak göz önünde bulundurulamaz. Verilen bilgiler yalnızca güvenli taşıma, kullanma, işleme, depolama, nakliyat, imha ve tahliye amacıyla tasarlanmıştır ve garanti veya kalite spesifikasyonu sayılamaz. Bu bilgiler yalnızca belirtilen madde/karışım için geçeri olup diğer maddelerle karıştırılması durumunda veya diğer bir proseste kullanılması halinde geçerli olmayabilir.

MALZEME GÜVENLİK BİLGİ FORMU
(MATERIAL SAFETY DATA SHEET)

UAT 2

2024

SAFETY DATA SHEET

UAT 2

SECTION 1. PRODUCT IDENTIFICATION

Product name : UAT 2

Recommended use of the chemical and restrictions on use

Recommended use : Automotive and industrial grease.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:
Not classified as a physical hazard under GHS criteria.
HEALTH HAZARDS:
Not classified as a health hazard under GHS criteria.
ENVIRONMENTAL HAZARDS:
Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:
No precautionary phrases.

Response:
No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:
No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used grease may contain harmful impurities.High-pressure injection under the skin may cause serious damage including local necrosis.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture: Mixture

Chemical nature: A lubricating grease containing highly-refined mineral oils and additives.
The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Zinc naphthenate	12001-85-3	Skin Sens.1B; H317 Eye Irrit.2; H319 Aquatic Chronic2; H411	0.1 - 0.9
Alkaryl amine	68411-46-1	Repr.2; H361	0.1 - 0.9
Alkyl thiadiazole	13539-13-4	Skin Irrit.2; H315 Skin Sens.1A; H317 Acute Tox.4; H332 Aquatic Chronic4; H413	0.01 - 0.09
Triazole derivative	91273-04-0	Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Acute2; H401 Aquatic Chronic2; H411	0.01 - 0.09

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	: Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.

Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Hazchem Code	:	NONE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Methods and materials for containment and cleaning up	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

		Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.

Storage

Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

Biological Limit Values (BLV) have not been established for this material.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.
Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/
Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/
Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/
Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp
L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:
Define procedures for safe handling and maintenance of controls.
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or subsequent recycle.
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.
If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be

treated in a municipal or industrial waste water treatment plant before discharge to surface water.
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Semi-solid at room temperature.
Colour	: Light brown
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
pH	: Not applicable
Dropping point	: 180 °C / 356 °F Method: IP 396
Melting / freezing point	: Not applicable
Initial boiling point and boiling range	: Data not available
Flash point	: Not applicable
Evaporation rate	: Data not available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Not classified as flammable but will burn.
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.900 (15 °C / 59 °F)
Density	: 900 kg/m3 (15.0 °C / 59.0 °F) Method: Unspecified
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: log Pow: > 6 (based on information on similar products)

Auto-ignition temperature	:	> 320 °C / 608 °F
Decomposition temperature	:	Data not available
Viscosity		
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	11 mm2/s (100 °C / 212 °F) Method: ASTM D445 100 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445
Explosive properties	:	Classification Code: Not classified
Oxidizing properties	:	Data not available
Surface tension	:	Data not available
Conductivity	:	This material is not expected to be a static accumulator.
Particle size	:	Data not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Exposure routes	:	Skin and eye contact are the primary routes of exposure

although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 rat: > 5,000 mg/kg
Remarks: Low toxicity
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg
Remarks: Low toxicity
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser.
Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Based on available data, the classification criteria are not met., Not a developmental toxicant., Does not impair fertility.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically

for this product.
Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Ecotoxicity

Product:

Toxicity to fish (Acute toxicity)	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Acute toxicity)	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae/aquatic plants (Acute toxicity)	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met.

Persistence and degradability

Product:

Biodegradability	: Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment.

Bioaccumulative potential

Product:

Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.
Partition coefficient: n-octanol/water	: log Pow: > 6Remarks: (based on information on similar products)

Mobility in soil

Product:

Mobility	: Remarks: Semi-solid under most environmental conditions., If

it enters soil, it will adsorb to soil particles and will not be mobile.
Remarks: Floats on water.

Other adverse effects

no data available

Product:

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.
Poorly soluble mixture., Causes physical fouling of aquatic organisms.
Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Do not dispose into the environment, in drains or in water courses.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

ADG
Not regulated as a dangerous good

International Regulations

IATA-DGR
Not regulated as a dangerous good

IMDG-Code
Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons	:	No poison schedule number allocated

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Other international regulations

The components of this product are reported in the following inventories:

TSCA	:	All components listed.
AIIC	:	Listed introduction

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Eye Irrit.	Eye irritation
Repr.	Reproductive toxicity
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date of preparation or review : 21.03.2023

Further information

Other information A vertical bar (|) in the left margin indicates an amendment from the previous version.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN